

Capillary Equipment

Wellhead Control Products, Inc. www.wellheadcontrol.com





CU Capillary Units

Custom designed and fabricated capillary units to meet your specific needs!



TRUCK, TRAILER, OR SKID MOUNTED

BUILT TO CUSTOMER SPECSIFICATIONS

The unit shown above features:

- PTO mounted hydraulic pumps with 100 gal reservoir
- Control Cabin with A/C, heat, and large windows
- Quick-load Reel system for wooden shipping spools, levelwind, & counter
- Crane with hydraulic out and down outriggers
- 10K Capillary injector head
- Side-door stripper

Other Possible Options \ Configurations

- **Trailer or Skid Mounted**
- **Diesel Power Packs**
- **Electric over hydraulic controls**
- Open air control panel

- Reel with fixed steel spool
- Fluid pump and chemical tank
- Hose reels

Call us today to discuss your particular needs

Wellhead Control Products, Inc.

501 N. Richey Pasadena, TX 77506 713,475,2283 800.457.1198



wellheadcontrol.com





Capillary Injector Heads



HYDRAULIC TENSION & TRACTION

10,000 LBS PULL

SIDE-DOOR STRIPPER

- 10,000 lbs. of continuous pull
- 5,000 PSI snubbing capacity
- Speeds from 6 ft to 200 ft per minute
- Rollered, single piece skate design
- Hydraulic traction and tension
- Clearance for 2" OD tools

- 5,000 PSI Side-door stripper
- Folding gooseneck
- Small package

Frame: 3' x 3' x 4' tall Gooseneck: 2.5' tall

Monkey boards: 2' long



Wellhead Control Products, Inc.

501 N. Richey Pasadena, TX 77506 713.475.2283 800.457.1198





Capillary Reels



WOOD OR STEEL SPOOLS

COUNTER & LEVELWIND

QUICK LOAD

- 4' Diameter shipping spools
- Quick load system, no need remove and stab the axle shaft
- Oversized pillow block bearings
- Hydraulic levelwind system
- Direct drive tubing counter

Available Options

- Permanently mounted Steel Spool
- Hydraulic lift levelwind arms
- Self-loading spool system
- Pump through rotating joints
- Disk brakes

Dimensions of frame: 5' x 5' x 4' tall



Wellhead Control Products, Inc.

501 N. Richey Pasadena, TX 77506 713.475.2283 800.457.1198

